

# Geodesic LED

Cable Suspension Mounted • Damp Location Listed **PROGRESS LED**

## Description:

Geodesic LED Collection Matte Black LED Mid-Century Modern Medium Pendant Hanging Light

## Specifications:

- Frosted Acrylic Diffuser
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 5 in W., 1.6 in ht., 5 in depth
- Swivel mounting strap for outlet box included
- 96 in of wire supplied 90 in

## Performance:

Number of Modules	1
Input Power	28 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	2,067/73 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	cCSAus Damp Location Listed Meets California Title 24 JA8-2019

# P500319-031-30



## Dimensions:

Length: 17-15/16 in  
 Diameter: 17-15/16 in  
 Height: 9-3/16 in  
 Overall Ht. W/Cables: 100.8 in

Frosted Acrylic Diffuser  
 Width: 6-15/16 in  
 Height: 0.039 in

# P500319-031-30

## Dimming Notes:

---

P500319-031-30 is designed to be compatible with many Triac/ELV controls.

The following is a partial list of known compatible dimmer controls.

## Dimming Controls:

---

Leviton\_6674

Lutron\_NTEVL-300

Lutron\_DVELV-300P

Lutron\_Caseta Wireless

Lutron\_SCL-153P

Lutron\_TGCL-153-PH-WH

Lutron\_MACL-153M

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.