

Everlume

Ceiling Mounted • Damp Location Listed **PROGRESS LED**

Description:

Everlume LED 48-inch Satin White Modern Style Linear Ceiling Panel Light

Specifications:

- Dimmable to 10% brightness (See Dimming Notes)
- Mounting backplate for outlet box included
- 6 in of wire supplied

Performance:


Number of Modules	1
Input Power	43 W
Input Voltage	120 VAC
Input Frequency	60 Hz
Lumens/LPW (Delivered)	3,184/74 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	cCSAus Damp Location Listed
	Meets California Title 24 JA8-2016

P810033-028-30



Dimensions:

Width: 47-3/4 in
Depth: 11-15/16 in
Height: 1-3/16 in



Dimming Notes:

P810033-028-30 is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Eaton AAL06

Lutron NTEVL-300

Lutron DVELV-300P

Lutron AYCL-153P

Lutron TGCL-153-PH-WH

Lutron MACL-153M

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

P810033-028-30