

Project Name

Location

Prepared By



Notes

## General

|                        |               |
|------------------------|---------------|
| Status                 | Active        |
| Watts                  | 11.5          |
| Fluorescent Equivalent | 32            |
| Volts                  | 120V          |
| Ballast Type           | Type B        |
| Shape                  | T8            |
| Base                   | Medium Bi Pin |
| ANSI Base              | G13           |
| Nominal Length         | 48            |
| Finish                 | Frosted       |
| CCT (Kelvin)           | 4000          |
| Temperature            | Cool White    |
| CRI                    | 80            |
| Lumens                 | 1750          |
| Beam Spread            | 180           |
| Dimmable               | Non-Dimmable  |
| Hours Rated            | 50000         |
| Lamp Type              | Linear        |
| Technology             | LED           |

## Electrical

|                         |                                                                                           |
|-------------------------|-------------------------------------------------------------------------------------------|
| Ballasting Requirements | Ballast Bypass; Direct wire 120-277V line voltage; No ballast or external driver required |
| Dimmable Down To        | N/A                                                                                       |
| Dimming Type            | N/A                                                                                       |
| Power Factor            | 0.9                                                                                       |
| Operating Temperature   | -25C (-13F) to a maximum of +45C (+113F)                                                  |

## Physical

|               |         |
|---------------|---------|
| MOL           | 48      |
| MOD           | 1       |
| Lens Finish   | Frosted |
| Lens Material | Glass   |
| Housing Color | White   |
| Weight (lb.)  | 0.85    |

## Additional Information

|                    |                                                                             |
|--------------------|-----------------------------------------------------------------------------|
| Additional Info    | Installation protection - will not light if ballast is not bypassed.        |
| Shatter-Proof Type | PET Coated                                                                  |
| Installation Notes | Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring |
| Warranty           | 5 Year Limited - T8 LED Bulbs - Ballast Bypass                              |

## Compliance

|                 |                  |
|-----------------|------------------|
| Safety Listing  | cULus Classified |
| Location Rating | Damp             |

|                |                                         |
|----------------|-----------------------------------------|
| Energy Star    | No                                      |
| DLC Approved   | Yes                                     |
| DLC ID         | PL20XAZLMN46                            |
| CEC Status     | Lawful for sale in California           |
| RoHS Compliant | Yes                                     |
| FCC Compliant  | Yes                                     |
| NSF Approved   | ETL Sanitation listed (conforms to NSF) |