

Project Name

Location

Prepared By



SATCO S13181

13.5W/LED/HID/ED17/840/E26/CL

Notes

(www) 10-09-2024 00:51:46

General

Status	Active
Watts	13.5W
HID Equivalent	50W
Volts	120V-277V
Shape	ED17
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80
Lumens	2000L
Beam Spread	320
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Ballasting Requirements	Ballast Bypass

Electrical

Operating Frequency	60Hz
Power Factor	0.9
Operating Position	Universal
Surge Protection	Built-in surge protection - 4KV
Operating Temperature	-30C (-22F) to +65C (+149F)

Physical

MOL	5.8
MOD	2.13
Weight (lb.)	0.17

Additional Information

Rated For Enclosed Fixture	Yes
IP Rating	IP65
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5 Year Limited - Hi-Pro

Compliance

Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Wet
CA T20 / T24 Rationale	Non-Compliant - <82 CRI
California Status	Non-Compliant
Title 20 / 24 Status	Non-Compliant
RoHS Compliant	Yes
FCC Compliant	Yes