## SATCO NUVO

Project Name

ocation Prepared By



Notes

wl 10-09-2024 00:51:40

Status	Active	
Watts	40W	
HID Equivalent	200W	
Volts	120V-277V	
Shape	ED37	
Base	Mogul Extended	
ANSI Base	EX39	
Finish	Clear	
CCT (Kelvin)	4000K	
Temperature	Cool White	
CRI	80	
Lumens	7500L	
Beam Spread	320	
Dimmable	Non-Dimmable	
Hours Rated	50000	
Product Category	LED HID	
Technology	LED	
Ballasting Requirements	Ballast Bypass	

Operating Frequency	60Hz
Power Factor	0.9
Operating Position	Universal
Surge Protection	Built-in surge protection - 4KV
Operating Temperature	-30C (-22F) to +65C (+149F)

Physical	
MOL	10.3
MOD	4.7
Weight (lb.)	0.64

Additional Information		
Rated For Enclosed Fixture	Yes	
IP Rating	IP65	
Installation Notes	Not for use in vapor tight fixtures.	
Warranty	5 Year Limited - Hi-Pro	

Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Wet
CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes