

Project Name

Location

Prepared By



## SATCO S16400

9T8/LED/HO-SIGN/24-840/BP

Notes

### General

|                        |                                |
|------------------------|--------------------------------|
| Status                 | Active                         |
| Watts                  | 9                              |
| Fluorescent Equivalent | 37                             |
| Volts                  | 120V-277V                      |
| Ballast Type           | Type B                         |
| Shape                  | T8                             |
| Base                   | Recessed Double Contact HO/VHO |
| ANSI Base              | R17d                           |
| Nominal Length         | 24                             |
| Finish                 | Frosted                        |
| CCT (Kelvin)           | 4000                           |
| Temperature            | Cool White                     |
| CRI                    | 83                             |
| Lumens                 | 1200                           |
| Beam Spread            | 330                            |
| Dimmable               | Non-Dimmable                   |
| Hours Rated            | 50000                          |
| Lamp Type              | Linear                         |
| Technology             | LED                            |

### Electrical

|                         |                                          |
|-------------------------|------------------------------------------|
| Ballasting Requirements | Ballast Bypass                           |
| Operating Frequency     | 50/60 Hz                                 |
| Dimmable Down To        | N/A                                      |
| Dimming Type            | N/A                                      |
| Power Factor            | 0.9                                      |
| Operating Temperature   | -30C (-22F) to a maximum of +45C (+113F) |

### Physical

|     |       |
|-----|-------|
| MOL | 21.88 |
| MOD | 1     |

### Additional Information

|                    |                                                                            |
|--------------------|----------------------------------------------------------------------------|
| Installation Notes | No ballast or external driver required; Direct wire 120-277V line voltage. |
| Warranty           | 5 Year Limited - T8 LED Bulbs - Ballast Bypass - Outdoor Temperature Rated |

### Compliance

|                 |                               |
|-----------------|-------------------------------|
| Safety Listing  | cULus Classified              |
| Location Rating | Damp                          |
| Energy Star     | No                            |
| CEC Status      | Lawful for sale in California |
| RoHS Compliant  | Yes                           |
| NSF Approved    | Yes - Approved                |

