## SATCO NUVO

Project Name

Location

Prepared By



## **SATCO S39673**

45W/LED/HID/4K/100-277V EX39

Notes

General	
Status	Active
Watts	45
Incandescent Equivalent	300
Fluorescent Equivalent	65
HID Equivalent	175
Volts	100V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Un-Lensed
CCT (Kelvin)	4000
Temperature	Cool White
CRI	80
Lumens	6300
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length 11 in. Width 8 in. Depth 8 in.
Ballasting Requirements	Ballast by-pass - Direct wire only 100 - 277V
Electrical	
Working Voltage	AC 100-277V
Operating Frequency	50/60 Hz
Dimmable Down To	N/A
Dimming Type	N/A
Dimming Type Power Factor	N/A 0.9
Power Factor	0.9 Universal
Power Factor Burning Position	0.9
Power Factor  Burning Position  Surge Protection	0.9 Universal Built-in surge protection - 4KV -20C (-4F) to a maximum of +40C
Power Factor  Burning Position  Surge Protection  Operating Temperature	0.9 Universal Built-in surge protection - 4KV -20C (-4F) to a maximum of +40C
Power Factor  Burning Position  Surge Protection  Operating Temperature  Physical	0.9 Universal Built-in surge protection - 4KV -20C (-4F) to a maximum of +40C (+104F)
Power Factor Burning Position Surge Protection Operating Temperature Physical MOL	0.9 Universal Built-in surge protection - 4KV -20C (-4F) to a maximum of +40C (+104F)
Power Factor Burning Position Surge Protection Operating Temperature  Physical MOL MOD	0.9 Universal Built-in surge protection - 4KV -20C (-4F) to a maximum of +40C (+104F)  8.81 3.34
Power Factor Burning Position Surge Protection Operating Temperature  Physical MOL MOD Lens Finish	0.9 Universal Built-in surge protection - 4KV -20C (-4F) to a maximum of +40C (+104F)  8.81 3.34 Clear
Power Factor Burning Position Surge Protection Operating Temperature  Physical MOL MOD Lens Finish Lens Material	0.9 Universal Built-in surge protection - 4KV -20C (-4F) to a maximum of +40C (+104F)  8.81 3.34 Clear Plastic
Power Factor Burning Position Surge Protection Operating Temperature  Physical MOL MOD Lens Finish Lens Material Housing Color	0.9 Universal Built-in surge protection - 4KV -20C (-4F) to a maximum of +40C (+104F)  8.81 3.34 Clear Plastic White
Power Factor Burning Position Surge Protection Operating Temperature  Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	0.9 Universal Built-in surge protection - 4KV -20C (-4F) to a maximum of +40C (+104F)  8.81 3.34 Clear Plastic White

**Enclosure Rating** 

IP Rating



IP64





Enclosed Rated Lamp



Compliance	
Safety Listing	cULus
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PLIHE970MYG6
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp







