

Project Name

Location

Prepared By



SATCO S8760

8W/LED/CFL/5CCT/E26

Notes

(www) 10-14-2024 01:00:14

General

Status	Active
Watts	8W
Fluorescent Equivalent	18W
Volts	120V-277V
Ballast Type	Type B
Shape	PL
Base	Medium
ANSI Base	E26
Finish	Frost
CCT (Kelvin)	2700K/3000K/3500K/4000K/5000K
Temperature	Warm White to Natural Light
CRI	83
Lumens	950L/975L/1000L/1050L/1050L
Beam Spread	120
Dimmable	Non-Dimmable
Hours Rated	50000
Operating Position	Universal
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	<20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	6.5
MOD	1.38
Weight (lb.)	0.19

Additional Information

Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - 10 hr per day

Compliance

Safety Listing	cULus - Certified; cULus - Listed
Location Rating	Damp
CA T20 / T24 Rationale	T20 Pending
RoHS Compliant	Yes
FCC Compliant	Yes