



# S9779

40W/LED/HID/PT/3000K/100-277V  
40 watt - Post Top LED; 3000K; Medium base; 100-277 volts

## Features

- For use in any post top fixture to provide light out and down only
- Replaces HID, CFL, and Incandescent
- Direct wire range voltage 100-277V

Specification note: Operating temperature range -20°C to 65°C;  
Operating Frequency 50-60Hz; Working Voltage AC 90-305V

| Minimum Compartment Size |           |           |
|--------------------------|-----------|-----------|
| Length                   | Width     | Depth     |
| 9.25 inch                | 9.25 inch | 8.27 inch |

Optional accessory: In-line surge protector [80-929](#)



S9779

| Item Number           | Product Line                                                      | UPC           | Input Voltage | Watts          | Base                | ANSI Base                   | Lamp Code                      |  |
|-----------------------|-------------------------------------------------------------------|---------------|---------------|----------------|---------------------|-----------------------------|--------------------------------|--|
| S9779                 | Hi-Pro                                                            | 045923097799  | 100 - 277     | 40             | Medium              | E26                         | 40W/LED/HID/PT/3000K/100-277V  |  |
| Dimmable/Non-Dimmable | Finish                                                            | MOL In Inches | MOD In Inches | Initial Lumens | Average Rated Hours | Kelvin Temp                 | Color                          |  |
| Non-Dimmable          | White                                                             | 5-1/2"        | 5-1/8"        | 5000           | 50000               | 3000                        | Soft White                     |  |
| CRI                   | Operating Temperature                                             | Pack          | Package Type  | RoHS Compliant | UL or ETL Listed    | UL Classification           | Warranty                       |  |
| 80+                   | Operating temperature: -20°C (-4°F) to a maximum of +45°C (113°F) | 12            | Box           | Yes            | Yes                 | cULus - Damp Location Rated | <a href="#">5 Year Limited</a> |  |



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051