

Project Name

Location

Prepared By



## SATCO S1960

50MR16/FLEXN 12V

Notes

### General

|              |                       |
|--------------|-----------------------|
| Status       | Active                |
| Watts        | 50                    |
| Volts        | 12V                   |
| Shape        | MR16                  |
| Filament     | C-8                   |
| Base         | Miniature 2 Pin Round |
| ANSI Base    | GU5.3/GX5.3           |
| CCT (Kelvin) | 2900                  |
| Temperature  | Warm White            |
| CRI          | 100                   |
| Beam Spread  | 38                    |
| Dimmable     | Yes Dimmable          |
| Hours Rated  | 2000                  |
| Lamp Type    | MR                    |
| Technology   | Halogen               |

### Electrical

|           |            |
|-----------|------------|
| Spot Type | FL - Flood |
| CBCP      | 1600       |

### Physical

|     |      |
|-----|------|
| MOL | 1.88 |
| MOD | 2    |

### Additional Information

|                 |                         |
|-----------------|-------------------------|
| Additional Info | UV Block                |
| Warranty        | Avg. Rated Hour Limited |

### Compliance

|                          |                                        |
|--------------------------|----------------------------------------|
| Safety Listing           | Not Listed                             |
| Location Rating          | Damp                                   |
| Energy Star              | No                                     |
| CEC Status               | Non-Compliant                          |
| CEC Compliant Substitute | S9496                                  |
| RoHS Compliant           | Yes                                    |
| SDS Sheet                | Halogen_Double_Ended_or_Pin_Based_Lamp |