

S39738

45W/LED/HID/4000K/100-277V E26 45 watt LED HID Replacement; 4000K; Medium base; 100-277

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
 Damp location IP64 rated
- For outdoor & indoor use
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cULus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in Surge Protection: 4KV

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size									
Length	Width	Depth							
8 inch	8 inch	11 inch							

Optional Accessories

- In-line surge protector 80-929
- Mog to med socket reducer (rated up to 600V) 92-410



S39738

S397	38	Hi-Pro	0-	045923397387		100	- 277	45	50	60/60Hz 30		WOO		65W	
HID Eq	uivalent	t Bas	Δ	NSI Base		Lam	ıp Cod	le		Dimmable Dimma		Finish	MOL II		
175	5W	Mediu	ım E	E26	45W/LI	ED/HID/4	000K/1	100-277V E	26	Non-Dimr	nable	White	8-1/2	' 3-11/32"	
Initia Lume		Average Hou			elvin emp	Color	CRI	Beam Spread [Burning	Position	Op	perating ⁻	Temperature	
630	300 50000		00	40	000	Cool White	80	300		1 /	· ·		. ,	a maximum of (+149F)	
Pack	Pack Ty	rage rpe	CE	CEC Status		Material RoHS Compliant		nt	UL or ETL Listed	UL Classification		ition	Warranty		
12	В	ох		Lawful for sale in California		Aluminu	ım	Yes		Yes	cULus - I	Damp Lo Rated	ocation	5 Year Limited	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051