



**Sunlite 49168-SU LED Slim Profile Outdoor Wall Pack Fixture, 50K - Super White, 8625 Lumen, 75 Watt, White Finish**

- **LED TECHNOLOGY** - Sunlite LED Slim Profile Downlight fixtures are designed to provide ample outdoor illumination. An adjustable base allows you to direct the light for optimal coverage. With 96 built-in LEDs they are an energy efficient and maintenance-free lighting solution with a long life span of up to 50,000 hours.
- **ENERGY EFFICIENT** - Using 75 watts of energy these fixtures have a low estimated yearly energy cost of \$9.03. (Based on 3 hours/day use at \$0.11/kWh) These fixtures will provide significant savings in electricity over their lifetime with no bulbs to replace.
- **MAXIMUM LIGHT OUTPUT** - Each fixture gives off a bright 8625 lumen with 5000K super white color temperature.
- **MULTIPLE OUTDOOR USES** - These commercial grade fixtures feature a weather-resistant aluminum body finished in white. Ideal for security and general purpose lighting along the perimeter of buildings, entryways, or anywhere extra lighting is needed.
- **ETL AND DLC LISTED** - These fixtures are ETL Listed for wet location installation and DLC Listed for quality and efficiency. They operate on 120-277 volt electrical service.



**General Characteristics**

<b>Fixture Life Hours</b>	50000 Hours
<b>Material</b>	Metal
<b>Lens Finish</b>	Clear
<b>Bulb</b>	Integrated LED
<b>Finish</b>	White
<b>Lumens Per Watt (LPW)</b>	115.00
<b>Life (based on 3hr/day)</b>	45.7
<b>Estimated Energy Cost</b>	\$9.03 per Year
<b>Safety Rating</b>	ETL Listed - Wet Location
<b>DLC</b>	True

**Fixture Characteristics**

<b>Number of Lights</b>	1 - Light
<b>Mounting</b>	Wall
<b>Use Location</b>	Outdoor

**Electrical Characteristics**

<b>Watts</b>	75
<b>Volts</b>	120-277
<b>Equivalent Watts</b>	250-400
<b>LED Chip Manufacturer</b>	Philips 3030
<b>Number of LEDs</b>	96
<b>Power Factor</b>	0.92
<b>Operating Temperature</b>	-40° to 40° C

**Light Characteristics**

<b>Brightness</b>	8625 Lumens
<b>Color Accuracy (CRI)</b>	70
<b>Light Appearance</b>	Super White
<b>Color Temperature</b>	5000K
<b>Beam Angle</b>	100°-80°

**Product Dimensions**

<b>Item Dimensions (in)</b>	(W) 9.64 (H) 10.43 (D) 4.25
<b>Package Dimensions (in)</b>	(W) 12.99 (H) 4.80 (D) 13.62

**Product Data**

<b>Item Number</b>	49168-SU
<b>Case Quantity</b>	6
<b>Barcode on SKU</b>	653703491684
<b>Barcode on Case</b>	10653703491681
<b>Brand</b>	SUNLITE
<b>Description</b>	LFX/SWP/75W/WH/50K
<b>DLC File Number</b>	PRVLA70X