

LFX-RL-2X4-55W-LED-MV-40K LOW PROFILE FIXTURE SUNL



2x4 55 Watt Mult-Volt Low Profile LED Troffer, Dimmable, Cool White

Description

The ELL offers the look and feel of a fluorescent luminaire with subtle soft direct elements, interest and depth across the ceiling plane with a contemporary look that blends with today's commercial spaces. The frosted acrylic lens provides a diffused luminance, with the effective combination of excellent light transmission and haze.

Features

- High performance optical engine delivers main beam focus through the integrated acrylic lens.
- Lumieo acrylic diffuser manages the balance of efficiency and aesthetics.
- Linear arrayed LED modules provide diffused, but effective illumination.
- LED light engine (optional) by LG Innotek, global leader in LED technology.
- UL listed and DLC approved.

Specifications

Housing

Low profile troffer body with white sloped side members.

Direct Optical Component.

High performance optical engine.

Diffuser Surround center "V" adds character.

Lumieo acrylic diffuser.

Luminaire Type

Recessed troffer 2'x2' and 2'x4' size.

Light Source

LED light engine includes 50 chip board and matched driver.



General Characteristics

Fixture Life Hours

50,000 Hours

Lens

Center Basket

Lens Material

Acrylic

Bulb

Integrated LED

Finish

White

Lumens Per Watt (LPW)

112.06

Life (based on 3hr/day)

45.7

Safety Rating

UL Listed

Dimmable

True

DLC

True

Fixture Characteristics

Collection

Low Profile

Style

Troffer

Shape

Rectangle

Number of Lights

1 - Light

Mounting

Recessed

Use Location

Indoor

Electrical Characteristics

Watts

52

Volts

120-277

Light Characteristics

Brightness

5827 Lumens

Color Accuracy (CRI)

84.4

Light Appearance

Cool White

Color Temperature

4000K

Product Dimensions

Size

2X4

Product Data

Item Number

90358-SU

Barcode on SKU

653703903583

Brand

SUNLITE

Description

LFX-RL-2X4-55W-LED-MV-40K

DLC File Number

P7GAAYE5