SYLVANIA Luminaires

ValueLED™ CCT Selectable Small Wall Pack

Application

The ValueLED Small Wall Pack luminaires are environmentally preferable LED alternatives to traditional HID luminaires, offering up to 68% in energy savings. Ideal in place of traditional luminaires, or as new installations, the Small Wall Pack series is offered in several wattages/lumen packages for illuminating building exteriors, outdoor corridors, walkways, and stairwells.

Benefits and Features

- CCT Selectable (3000K, 4000K, or 5000K) enabled through switch located inside fixture
- IP65 and IK08 rated body with aluminum backplate and polycarbonate lens offers easy mounting, reducing installation and maintenance costs
- DLC listing ensure energy efficiency and provide uniform and even lighting
- Photosensor included provides additional energy savings
- Up to 120 LPW
- Offered in 20 watts
- Non-cutoff distribution
- Energy savings up to 68%

Electrical

- 120-277Vac
- Power Factor > 0.9
- THD < 20%

Rated Life

150,000 hours (L₇₀)

Warranty

- 5-year
- NLB Trusted Warranty Program

Operating Temperature

-40°F to +104°F (-40°C to +40°C)

Type Project Notes
Notes
110100
Date



Wattage Comparison

Traditional Source	Traditional System Wattage	LED System Wattage	Energy Savings
50W HPS	62	20	68%
50W MH	62	20	68%

Certifications and Listings

- cULus - DLC RoHS - IK08
- IP65 - TAA Compliant
- FCC

Installation

Luminaire mounts to exterior wall. Level included in back plate.
















Ordering Guide

SMWLPAK	2N	/ 020	UNV	7	SC2	/	NC	BZ	/	P
Product Name	Generation/Distribution	Wattage	Voltage	CRI	Color Temp		Distribution	Color/Finish		Options
SMWLPAK =	2N = Generation 2, non-cutoff	020 = 20 Watts	120-277V	CRI = >70	SC2 = 3000, 4000		NC = Non-cutoff	BZ = Bronze Finish		P = Motion/
Small Wall Pack					or 5000K					Daylight Sensor

Ordering Information

ltem		Power	Input		Color		Total Fixture			
Number	Ordering Abbreviation	(W)	Voltage (V)	CRI	Temp.	Distribution	Lumens	LPW	Options	DLC
61750	SMWLPAK2N/020UNV7SC2/NCBZ/P	20	120-277	>70	3000, 4000 or	Non-cutoff	1800	120	Motion/daylight	Standard
					5000K				sensor	

Physical Information



LEDVANCE LLC 200 Ballardvale Street Wilmington, MA 01887 USA Phone 1-800-LIGHTBULB (1-800-544-4828) www.ledvanceUS.com

SYLVANIA and LEDVANCE are registered trademarks.

All other trademarks are those of their respective owners.

Licensee of product trademark SYLVANIA in general lighting.

Specifications subject to change without notice.







