

SYLVANIA Luminaires

UltraLED™ Retrofit Door Kit

Application

Ideal for illuminating office, retail, hospitality, or general purpose areas.

Benefits and Features

- Up to 130 LPW
- 3500K, 4000K and 5000K color temperature
- CRI >80
- Offered in 18, 23 and 33 watts
- Energy savings up to 60%

Electrical

- The luminaire is designed to operate through the 120-277 V_{AC} (UNV)
- The power factor is ≥90%
- THD is ≤20%
- 0-10V dimmable

Rated Life

- >100,000 hours (L₇₀)

Warranty

- 5-year
- NLB Trusted Warranty Program

Ambient Operating Range

- -4°F to +104°F (-20°C to +40°C)

Certifications and Listings

- cULus listed for damp applications
- RoHS
- FCC
- DLC 5.1

Installation

- Intended for installation in existing troffers



Wattage Comparison

Traditional Source	Traditional System Wattage	LED System Wattage	Energy Savings
3 x 17W T8	48	23	52%
2 x U31 T8	56	23	59%
3 x 28W T8	73	33	55%
3 x 32W T8	83	33	60%



Catalog #	Type
Project	
Comments	
Prepared by	

Ordering Guide

RDORKIT	3A	/ XX	UNV	D	8	XX	/ XX	U	/ WH
Product Name	Generation	Wattage	Voltage	Dimming	CRI	Color Temp	Dimensions	Mounting	Color/Finish
RDORKIT	3A	18 = 18 Watts 23 = 23 Watts 33 = 33 Watts	UNV = 120-277V	D = 0-10V Dimming	8 = >80	35 = 3500K 40 = 4000K 50 = 5000K	22 = 2x2 24 = 2x4	U = Universal Mounting	WH = White

Ordering Information

Item Number	Ordering Abbreviation	Wattage	Nominal Voltage	Dimming	CRI	Color Temp	Dimensions	Total Fixture Lumens	LPW	DLC	SKU qty	CS qty	MTD*
Lower-Wattage Versions													
61055	RDORKIT3A018UNVD83522UWH	18	120-277	0-10V	>80	3500K	2x2	2400	125	Prm	1	1	MTD
61056	RDORKIT3A018UNVD84022UWH	18	120-277	0-10V	>80	4000K	2x2	2400	125	Prm	1	1	MTD
61058	RDORKIT3A023UNVD83524UWH	23	120-277	0-10V	>80	3500K	2x4	3000	126	Prm	1	1	MTD
60616	RDORKIT3A023UNVD83522UWH	23	120-277	0-10V	>80	3500K	2x2	2900	126	Prm	1	1	—
61099	RDORKIT3A023UNVD83522UWH**	23	120-277	0-10V	>80	3500K	2x2	2900	126	Prm	24	24	—
60617	RDORKIT3A023UNVD84022UWH	23	120-277	0-10V	>80	4000K	2x2	2900	126	Prm	1	1	—
60618	RDORKIT3A023UNVD85022UWH	23	120-277	0-10V	>80	5000K	2x2	2900	126	Prm	1	1	—
60619	RDORKIT3A033UNVD83524UWH	33	120-277	0-10V	>80	3500K	2x4	4100	125	Prm	1	1	—
60620	RDORKIT3A033UNVD84024UWH	33	120-277	0-10V	>80	4000K	2x4	4100	125	Prm	1	1	—
60621	RDORKIT3A033UNVD85024UWH	33	120-277	0-10V	>80	5000K	2x4	4100	125	Prm	1	1	—

*Made To Order

**This item can only be returned in full pallets.

Photometrics

Average Illuminance (FC) at 30" AFF and avg/min uniformity


80/50/20 Reflectances

Calculations are based on 110ft x 50ft area

			8 ft Mounting Height			10 ft Mounting Height			12 ft Mounting Height		
			On Center Fixture Spacing								
			8'x10'	10'x10'	10'x12'	8'x10'	10'x10'	10'x12'	8'x10'	10'x10'	10'x12'
2'x2'	23W	RDORKIT3A023UNVD83522UWH	36fc/1.5	30fc/1.3	25fc/1.9	35fc/1.5	29fc/1.4	24fc/1.7	34fc/1.6	28fc/1.5	23fc/1.7
		RDORKIT3A023UNVD84022UWH	36fc/1.5	30fc/1.3	25fc/1.9	35fc/1.5	29fc/1.4	24fc/1.7	34fc/1.6	28fc/1.5	23fc/1.7
		RDORKIT3A023UNVD85022UWH	36fc/1.5	30fc/1.3	25fc/1.9	35fc/1.5	29fc/1.4	24fc/1.7	34fc/1.6	28fc/1.5	24fc/1.7
2'x4'	33W	RDORKIT3A033UNVD83524UWH	50fc/1.5	41fc/1.3	35fc/1.9	48fc/1.6	40fc/1.4	34fc/1.7	46fc/1.6	39fc/1.5	32fc/1.7
		RDORKIT3A033UNVD84024UWH	50fc/1.5	42fc/1.3	35fc/1.9	49fc/1.6	41fc/1.4	34fc/1.7	47fc/1.6	39fc/1.5	33fc/1.7
		RDORKIT3A033UNVD85024UWH	50fc/1.5	42fc/1.3	35fc/1.9	49fc/1.6	41fc/1.4	34fc/1.7	47fc/1.6	39fc/1.5	33fc/1.7

Physical Information

Luminaire Description	(A) Length (in.)	(B) Width (in.)	(C) Height (in.)
2x2	23.8	23.9	2.4
2x4	47.8	23.9	2.4



LEDVANCE LLC
181 Ballardvale Street, Suite 203
Wilmington, MA 01887 USA
Phone 1-800-LIGHTBULB (1-800-544-4828)
www.ledvanceUS.com

SYLVANIA and LEDVANCE are registered trademarks.
All other trademarks are those of their respective owners.
Licensee of product trademark SYLVANIA in general lighting.
Specifications subject to change without notice.



SCAN TO FOLLOW US
ON SOCIAL MEDIA

