

The Q Series General Purpose Strip (QGP) features a lightweight extruded aluminum body while maintaining a durable construction, a classic 4FT length, and up to 7,425 lumen output. With an efficiency of 135 lumens per watt, the QGP is designed to deliver a robust performance while maximizing energy savings.

TCP's Quick Connect System has been incorporated into the design standard. This allows for beautiful long continuous runs of light without the need for extra parts or accessories. The Quick Connect System does not stop at an efficient mechanical connection. The QGP also offers Quick Connect daisy chain 5-wire cable accessories.

Reasons to choose the Q Series General Purpose Strip from TCP

- TCP Quick Connect System
- Lightweight extruded body for easy install

Ideal Applications

- High ceilings
- Commercial settings
- Industrial settings
- Retail

- Warehouses
- Architectural settings









Q Series General Purpose Strip

Specifications

Input Line Voltage	120-277 VAC
Input Line Frequency (Hz	50/60Hz
Wattage (W	
Lumens (L	4725L/6075L/7425L
Lumens per Watt (LPW)	>135 LPW (80 CRI)
Rated Life	
Minimum Starting Temperature	20°C (-4°F)
Maximum Operating Temperature	
CRI	
Power Factor	>0.95
THD	
Ratings	cULus, damp location rated
Controls	

Features

- Lightweight, quick install construction
- Standard frosted lens for glare control
- No shadows for smooth, even lighting
- Damp location rated
- 0-10V smooth, no-flicker dimming
- Operating temperature: -4°F to 122°F
- TCP Quick Connect System
- Long 50,000 hour rated life
- Wide beam spread due to angled LED design providing clean cut off



Hardware Included

- Cable Hang Kit
- TCP's Quick Connect System

Installation

Suspended installation. Before installation, please consult your local ordinances and building codes.

Catalog Ordering Matrix Example: QGP4UZDA250K					
FAMILY	LENGTH	VOLTAGE	CONTROLS	LUMEN PACKAGE (Power) ¹ , ²	сст
QGP - QGP General Purpose Strip	4 - foot	U - 120-277V	ZD – 0-10V Dimming	A2 - 4725L (35W) A3 - 6075L (45W) A4 - 7425L (55W)*	40K – 4000K CCT 50K – 5000K CCT

¹ Approximate lumen output. Actual performance may vary based on CCT, options selected and end use application.

Field Installed Accessories

- Q5DAISY4FT TCP's Quick Connect System
- QTLSMOUNT1 Surface Mount Kit











² Actual wattage may differ by +/- 10%. *55W Model is selectable: 35/45/55W.

Wireline Dimensions



TCP Quick Connect System

Step 1: Step 2: Step 3:



Align male and female ends of the Quick Connect triangles



Slide together to fasten



Fasten locking screw until tight



Step 5:



Mechanical connection complete



Use Q5DAISY4FT Quick Connect cable to daisy chain units together

NOTE:

Electrical Daisy Chain Capabilities using Q5DAISY4FT: 55W model = 15 units in series







TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:	Catalog Number:
Date:	Туре:
Model:	Notes:
Project:	TCD.
Rep:	TCP we know light.™