



4113P; 4113PBE; 4113PBES

APPLICATION and PERFORMANCE SPECIFICATION

Description: Magnetic ballast for (1) CFT13W/GX23 or (1) CFQ13W/GX23 compact fluorescent lamp

• Line Voltage: 120vac +/-10%, 60Hz

• Pre-Heat

Model	Line Volts	Input Watts	Nominal Line Amps	Starting Current(Amps)	Power Factor	Ballast Factor	Ballast Efficacy Factor	Power Factor	THD	Crest Factor
4113P	120	14	0.24	0.36	> .50	.90	6.43	NPF	< 10%	<1.7
4113PBE	120	14	0.24	0.36	> .50	.90	6.43	NPF	< 10%	<1.7
4113PBES	120	14	0.24	0.36	> .50	.90	6.43	NPF	< 10%	<1.7

Application and Performance Specification Information Subject to Change without Notification.

Performance:

- Meets ANSI Standard C82.11-1993
- Class P Thermally Protected

Safety:

- No PCB's
- UL listed
(Class P, Indoor and Type 1 Outdoor)
- CSA Certified

Application:

- Minimum Starting Temperature: 32° F, 0° C
- Maximum Case Temperature: 90° C
- Sound Rated: A
- Leads: Side Exit
BE - Bottom Exit
BES - Bottom Exit w/Studs (Studs 2" O.C.)

Physical Parameters

Length: 3.13"
Width: 1.84"
Height: 1.42"
Weight: 0.70 lbs.
Lead Length: All Leads 12" (± 1")
Bottom Exit: All Leads 8" (± 1")
Can Colors: White
Qty/Carton: 40

Warranty:

Universal Lighting Technologies, Inc., warrants to the purchaser that each magnetic ballast will be free from defects in material or workmanship for a period of 2 years from date of manufacture when properly installed and under normal conditions of use. Call 1-800-BALLAST x801 for technical assistance.

Manufactured in North America

Ballast Case must be grounded.
Install in accordance with the
National Electrical Code.

