




Specification Sheet

Input Volts	480				
Regulation					
Line Volts	±10%				
Lamp Watts	±10%				
Power Factor (min)	90%				
Input Watts	1080 W				
NOM. Open Circuit Voltage	410 V				
Line Current (Amps)					
Operating	2.30				
Open Circuit	1.55				
Starting	1.40				
Recommended Fuse (Amps)	6				
Lamp Dropout Voltage (Line)	320 V				
UL Temperature Ratings					
Insulation Class	H (180°C)				
Temperature Code	D				
MIN. Starting Temperature	-22°F -30°C				
CAPACITOR Specifications					
Microfarads	24 uf				
Volts (min.)	480 V				
60Hz Test Procedures					
High Potential Test 1 Minute	2000 V				
High Potential Test 1 Second	2500 V				
Secondary Open Ckt Voltage (V)	365 - 455				
Secondary Current Shorted (A)	4.80 - 5.85				
Input Operating Current (A)	2.05 - 2.55				
Input Open Circuit Current (A)	0.75 - 2.20				
Input Short Circuit Current (A)	1.00 - 1.60				
Core and Coil Specifications					
Dimension A	2.85 in				
Dimension B	4.75 in				
Weight	22.0 lbs				
Lead Lengths (inches)	12-14				
Coil Material (Pri. / Sec.):	Cu / Al				



Capacitor: 005-2779-MF **Ignitor: None**

Temp Rating: 90 °C
Height: 3.90 in
Width / Diameter: 2.91 in



This Ballast does not require a Ignitor

For alternate capacitor construction consult sales

Data is based upon tests performed by universaldouglas in a controlled environment and is representative of relative performance. Actual performance may vary depending on operating conditions. Specifications are subject to change without notice.

Universal Lighting Technologies

51 Century Blvd. Suite 230 - Nashville, TN 37214

Phone 1-800-225-5278 Fax 1-800-206-0035

www.unvlt.com

2/2/2022