

14W LED Retrofit Lamp

Order Code: LP26748



Description

Venture Lighting's LED Retrofit lamps are the ideal upgrade solution to traditional HID lamp technologies. Venture's LED Retrofit lamps are a simple energy saving solution for providing significant maintenance savings. The integrated driver design is an ideal upgrade from traditional technologies.

Features & Benefits

- Replaces MH or HPS up to 70W*
- Replaces CFL up to 42W*
- 5 year warranty
- Universal burn position
- Easy installation
- Reduced maintenance costs
- *Note: It is the customer's responsibility to verify that the lamp compartment meets the minimum required lamp compartment dimension of 6 " diameter by 8.5" long.

Applications

- · Post top
- Wall pack
- Area Lighting
- Flood lighting
- · Garage lighting
- General illumination

Notes

- The use of an external surge protection device is recommended.
- Operating temp. range between -40°F and 122°F (-40°C and 50°C).
- Suitable for use in dry and damp environments.
- Suitable for use in portable, surface mounted and ceiling luminaires.
- \bullet Suitable for use in open and enclosed luminaires with minimum lamp compartment dimensions of 6 inch diameter x 8.5 inch deep.
- Do not use where exposed to water or outdoors without an appropriate enclosed luminaire.
- Lamps have clear polycarbonate cover lenses

| Product Performance | |
|------------------------------------|--------------------------------|
| Input Power (W) | 14 |
| Initial Lumens | 1680 |
| Lumens/Watt | 120 |
| Correlated Color Temperature (CCT) | 3000K |
| Color Rendering Index (CRI) | 80 |
| Life Hours | 50000 |
| Minimum Lamp Compartment Size | 6" Dia by 8.5" long |
| Dimming | No |
| Operating Temperature Range | -40°F to 122°F (-40°C to 50°C) |

| Physical Characteristics | |
|--------------------------|------------------|
| Base Type | Medium, (E26) |
| Overall Length A | 5.75" (146mm) |
| Diameter B | 2.76" (70mm) |
| Weight | 0.67 lbs (303 g) |

| Electrical Characteristics | |
|----------------------------|----------------------|
| Input Voltage Range | 100V-277V; 50/60Hz |
| Driver | Internal within lamp |
| Power Factor | >0.90 |
| THD | <20% |

| Regulatory | Qualifications |
|------------|----------------|
|------------|----------------|


cULus Listed


Accessories

SP12714 - 120-277V Surge Protector



Venture 14W LED Retrofit Lamp





(800) 451-2606 Fax: (800) 451-2605 7905 Cochran Rd, Suite 300 Glenwillow, Ohio 44139 E-mail: Venture_Lighting@VentureLighting.com VentureLighting.com

