

T8 Ballast Bypass LED Lamp

Operates with Direct Line Voltage - No Ballast Needed

Item Number 03854

Specifications		
Energy Used (Watts)	15	
Domestic Code	LED 15T8/48"/50 Ballast Bypass	
Input Voltage	120/277	
Brightness (Lumens)	1800	
Average Rated Hours	50,000	
Life in Years (3 hrs./day)	45.6	
Life in Years (12 hrs./day)	11.4	
Light Appearance (Kelvin)	5000	
CRI	82	
Efficacy (LPW)	120	
Number of LED Modules	80	
Minimum Starting Temperature	20°C/-4°F	
Estimated Yearly Energy Cost*	\$1.81	
Package Type	Sleeve	
Can be used anywhere a T8 or T12 fluorescent lamp is used.		



Can be used in totally enclosed fixtures.

_		
Finish	Frost	
Color Designation	Daylight	\
Base	G13 (Medium BiPin)	
MOI	48"	















Warning

- Turn power off before inspection, installation, or removal.
- Risk of electric shock Do not use where exposed to water or weather.
- Do not open no user serviceable parts inside.
- This device is not intended for use with emergency exit luminaires or emergency exit lights.
- This device complies with Part 15 of the FCC rules and has been tested and found to comply with the limits for a Class B digital device. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. Any changes or modifications not expressly approved by the manufacturer could void the user's authority to operate the equipment.

*Based on 3 hrs./day 114/kWh - Cost depends on rates and use.

Specifications are subject to change without notice, please visit www.westinghouselighting.com for latest information.

Call 1-800-999-2226 or visit www.westinghouselighting.com.

(22), WESTINGHOUSE, and INNOVATION YOU CAN BE SURE OF are trademarks of Westinghouse Electric Corporation. Used under license by Westinghouse Lighting. All Rights Reserved.