

T8 Universal Ballast Bypass LED Lamp

Operates with Direct Line Voltage - No Ballast Needed

Specifications

Operates in both singled-ended and double-ended ballast bypass wiring configurations.

When used in a single-end power configuration, the lamps must be used with non-Shunted tombstones. When used in a double-end power configuration, the lamps can be used with either shunted or non-shunted tombstones.

Can be used anywhere a T8 or T12 fluorescent lamp is used. Can be used in totally enclosed fixtures.

Physical Characteristics

Color Designation	Cool White
Finish	Frost
Base	G13 (Medium BiPin)
MOL	48"















Warning

- Turn power off before inspection, installation, or removal.
- Risk of electric shock Do not use where exposed to water or weather.
- Do not open no user serviceable parts inside.
- This device is not intended for use with emergency exit luminaires or emergency exit lights.
- This device complies with Part 15 of the FCC rules and has been tested and found to comply with the limits for a Class B digital device. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. Any changes or modifications not expressly approved by the manufacturer could void the user's authority to operate the equipment.

*Based on 3 hrs./day 11¢/kWh - Cost depends on rates and use.

Specifications are subject to change without notice, please visit www.westinghouselighting.com for latest information.

(W), WESTINGHOUSE, and INNOVATION YOU CAN BE SURE OF are trademarks of Westinghouse Electric Corporation. Used under license by Westinghouse Lighting. All Rights Reserved.