Catalog # **30435-SU**
F54T5/835/HO

ST Series

Sunlite 54 Watt T5 High Output High Performance Straight Tube, Mini Bi-Pin Base, Neutral White

T5 High Output High Performance Straight Tube



DESCRIPTION:

Sunlite fluorescent lamps are very popular for use in office and other lighting applications. The characteristics of fluorescent lamps vary type of lamp. Fluorescents lamps are used so widely due to their low operating costs and because they are efficient, last for years, and are high quality and rapid starting. Fluorescent lamps can cost significantly less to operate over their lifetime than incandescent lamps. Life ratings for fluorescent lamps range from 6,000 to 36,000 hours based on the industry standard of 3 burning hours per start. Also, rapid start and instant start lamps typically start within 1 second of being turned on. The High Perfomance and High Output versions also give you and even better efficacy and energy efficiency. Look for a higher CRI for improved light quality. Sunlite 30435-SU F54T5/835/HO 3500K Color Temperature T5 High Output Hight Performance Straight Tube Fluorescent 54 Watt lamp features a Mini Bi Pin base, provides a light output of 5000 lumens at a Color Rendering Index (CRI) of 82 and can last an average of 20000 hours.

FEATURES:

- *54-Watt*
- *3500K Color Temperature*
- *20,000 hour average lamp life*
-
-

sunlite®

Catalog # **30435-SU**
F54T5/835/HO

SPECIFICATIONS:

General Characteristics

Bulb Shape	*T5*
Average Rated Hours	*20000*
Base	*Miniature Bi-Pin (G5)*
Average Life Span Years	*18*

Electrical Characteristics

Watts	*54*

Light Characteristics

Lumens Brightness	*5000*
Color Rendering Index CRI	*82*
Emitted Color	*Neutral White*
Color Temperature Kelvin	*3500K*

Additional Features

Rohs Compliant	*Yes*

Product Dimensions

Size	*4 Foot*
MOL (in)	*45.80*
Diameter (in)	*0.625"*
Item Dimension (in)	*(W) 0.6 (H) 0.6 (D) 45.5*
Package Dimension (in)	*(W) 0.64 (H) 0.64 (D) 45.8*
Package Weight (lb)	*0.260*

Product Data

Case Unit Rate	*40*
Pack Size	*1*
Item UPC	*653703304359*

RoHS Compliant

VARIATIONS:


30435-SU


30430-SU


30440-SU


30445-SU


30450-SU

Item Number	Description	Watts	Lumens	CRI	Kelvin Color	Hours	Pack
30435-SU	F54T5/835/HO	54	5000	82	3500K NW	20000	1
30430-SU	F54T5/830/HO	54	5000	82	3000K WW	20000	1
30440-SU	F54T5/841/HO	54	5000	82	4100K CW	20000	1
30445-SU	F54T5/850/HO	54	5000	82	5000K SW	20000	1
30450-SU	F54T5/865/HO	54	5000	82	6500K DL	20000	1