GE Lighting

62718 - GE LFL UltraMax™ Electronic High Efficiency Multivolt Instant Start Ballast

GE232MAXP480-H

- Energy saving high efficiency instant start electronic ballast (> 90%) - NEMA premium
- GE 3-Stage 3G Transient Suppression - Meets IEEE/ANSI C Low line to line transient capability up to 6KV
- UL 55C Ambient Rating
- Anti-striation circuitry reduces striations with energy saving lamps
- Cold temperature -20F Minimum Starting Temperature

Product Photo



SAFETY & PERFORMANCE

- cUL_Listed
- FCC_CS_NCons
- UL_Cls_P
- UL_Listed
- UL_Type1_Out
- UL_Type_HL
- NEMA_Pre
- High_Temp_App
- C_max_wty_temp

CAUTIONS & WARNINGS

Warning

Risk of Electric Shock

Properly ground ballast and fixture.

Turn power off before servicing--see instructions.

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)	Crest Factor (<=)	THD% (<=)	Min. Starting Temp (F/ C)
F32T8	1	480	45	0.1	1.39	3	0.88	1.7	15	-22
F32T8	2	480	73	0.16	1.18	2	95.0	1.7	10	-22
F32T8/WM	2	480	68	0.15	1.16	2	0.92	1.7	10	50
F32T8/WM	1	480	42	0.1	1.37	3	0.88	1.7	15	50
F28T8	1	480	41	0.09	1.35	3	88.0	1.7	15	50
F28T8	2	480	64	0.14	1.13	2	0.92	1.7	10	50
F32T8/25W	1	480	38	0.09	1.34	4	0.88	1.7	15	50
F32T8/25W	2	480	59	0.13	1.11	2	0.92	1.7	10	50
F25T8	2	480	58	0.13	1.17	2	0.92	1.7	10	-22
F25T8	1	480	38	0.09	1.38	4	0.88	1.7	15	-22
F17T8	2	480	42	0.09	1.18	3	0.88	1.7	15	-22
F17T8	1	480	28	0.07	1.39	5	0.8	1.7	20	-22
F36T8	1	480	39	0.09	1.02	3	0.88	1.7	15	50
F36T8	2	480	61	0.14	0.85	1	0.92	1.7	10	50
F40T8	1	480	58	0.13	1.32	2	0.92	1.7	10	0