PHILIPS

Lighting



T8

8.5T8/COR/24-835/MF11/G/BAA 25/1

Philips MainsFit (UL Type B) T8 LED lamps use a double-ended design which significantly simplifies installation, saving time and costs. This product is proudly manufactured in the USA and is BAA (Buy American Act) compliant. This product can replace either T8 or T12 lamps in fixtures containing shunted or non-shunted G13 (medium bi-pin) lamp holders. Available in 4ft and 2ft lengths.

Product data

General information	
Base	G13 [Medium Bi-Pin Fluorescent]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	50000 h
Switching Cycle	50000
Buy American Compliant Products	Yes
Tier	CorePro

Light technical	
Color Code	835 [CCT of 3500K]
Beam Angle (Nom)	240 °
Initial lumen (Nom)	1100 lm
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3500 K
Luminous Efficacy (rated) (Nom)	129.00 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	8.5 W
Lamp Current (Max)	75 mA
Lamp Current (Min)	36 mA
Wattage Equivalent	17 W
Starting Time (Nom)	0.9 s
Warm Up Time to 60% Light (Nom)	0.9 s
UL Type	Type B - bypass the ballast
Power Factor (Nom)	0.9
Voltage (Nom)	120-277 V

Temperature	
T-Ambient (Max)	113 °F
T-Ambient (Min)	-4 °F
T-Storage (Max)	149 °F
T-Storage (Min)	-40 °F
T-Case Maximum (Nom)	122 °F

Controls and dimming	
Dimmable	No

Mechanical and housing	
Bulb Finish	Frosted
Bulb Material	Glass

T8

Product Length	23-5/8 in
Bulb Shape	Tube, double-ended

Approval and application

Energy Saving Product	Yes
Approbation Marks	RoHS compliance UL certificate DLC compliance
Energy Consumption kWh/1000 h	- kWh

Product data

Order product name	8.5T8/COR/24-835/MF11/G/BAA 25/1

EAN/UPC - Product	046677563752
Order code	563759
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	929002497904
Net Weight (Piece)	0.249 lb
Model Number	9290024979

Dimensional drawing



Product	D1	D2	A1	A2	A3
8.5T8/COR/24-835/ MF11/G/BAA 25/1	1-1/16 in	1-1/8 in	23-1/4 in	23-1/2 in	23-13/16 in

8.5T8/COR/24-835/MF11/G/BAA 25/1

Photometric data



LEDtube COR 11W G13 1650lm 835



LEDtube COR 8,5W G13 1100lm 835

Photometric data



LEDtube COR 11W G13 1650lm

Lifetime



Life Expectancy Diagram



FailureRate



LEDtube COR 8,5W 50K LumenVsTc



Lumen Maintenance Diagram

T8

Lifetime



LifetimeVsTc

© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.