A19 9W DIM. TITANIUM LED SERIES

GREENCREATIVE

PRO



9W REPLACES



60W Inc.

80% Energy Savings

$151 Savings per lamp*

- **Exceptional efficacy 89 LPW in Soft White**
- **40% more energy savings than CFL**
- **Comfortable warm diffused light**
- **Natural A-lamp shape fits all applications**
- **Ideal for lamps with shades**
- **Suitable for use in totally enclosed fixtures**

25,000 H

DIMMABLE

89 LPW EFFICACY

3 YR WARRANTY

82 CRI (Ra)

ENCLOSED**

c UL us LISTED

lighting facts LED Product Partner


LM 79 LM 80 TM 21 IES

A19 PRODUCT FEATURES


Suitable for Enclosed Fixtures

This A19 is suitable for use in totally enclosed fixtures and capable of operating in a broad range of applications. Whether it is installed in fully enclosed flushmounts or sconces, this lamp's advanced thermal design ensures optimal performance over the course of its lifetime.

ENCLOSED



Exceptional Efficacy



At 89 LPW, this lamp's efficacy is higher than the Tier 1 LED A19 60W replacement industry average and exceeds new ENERGY STAR 2.0 requirements. This energy-saving performance makes this lamp a smart retrofit choice for incandescent and CFL bulbs.

A19 9W DIM. TITANIUM LED SERIES


GREENCREATIVE

APPLICATIONS


General Lighting



Downlighting



Uplighting



Ref.#:DS170-A19-9W

SPECIFICATIONS

Product Model	97780 9A19DIM/827	97781 9A19DIM/830	97782 9A19DIM/840
Type	A19	A19	A19
Base	E26	E26	E26
Power (W)	9	9	9
Voltage - Frequency	120V 60Hz	120V 60Hz	120V 60Hz
Color Temp. (ANSI)	Soft White 2700K	Warm White 3000K	Cool White 4000K
CRI (Ra) (typ.)	82	82	82
Typical lumens (lm)	800	820	860
Efficacy (LPW)	89	91	96
Beam Angle	300°	300°	300°
Dimmable	Yes**	Yes**	Yes**
Power Factor	0.9	0.9	0.9
Rated Lifetime - L70 (hrs.)	25,000	25,000	25,000
Dia. x MOL	2.36"x4.41" (60x112mm)	2.36"x4.41" (60x112mm)	2.36"x4.41" (60x112mm)
Weight (lb. / g)	0.10lb. / 45g	0.10lb. / 45g	0.10lb. / 45g

* Savings per lamp based on $0.11 / kw energy cost, 12 hrs / day lamp usage, $2 incandescent with 1000-hr lifetime, $16 LED with 25,000-hr lifetime

** Suitable for use in totally enclosed fixtures

*** Suitable for damp locations. Not for use where directly exposed to weather or water