naturaled®

CRL CCT3 COMMERCIAL DOWNLIGHT

PROJECT:	
SCHEDULE:	**DATE:**
PREPARE BY:	
NOTES:	

DESCRIPTION

naturaLED® Commercial Recessed Light (CRL) is a commercial grade downlight fixture with CCT3 color temperature selectable. This Energy Star qualified downlight is a simple way to replace incandescent and fluorescent recessed lamps. Designed as an energy efficient lighting solution for the industry's popular 6" / 8" /10" recessed downlight fixtures. Easy installation with adjustable wattages and offering up to 2,700 lumens.

APPLICATIONS

Commercial, Kitchen, Basement, Residential, Hospitalities



Wet Location

5 YEAR WARRANTY

ADJUSTABLE WATTAGE 3

3 CCT SELECT

Rated Life 50,000 Hours
Warranty 5 Years

FEATURES

- Energy Star
- Wet Location
- IC Rated
- Air-Tight Rated
- UL Listed
- Color Temp Selectable: 3000K, 4000K, 5000K
- Wattage Selectable (3 Wattages)
- Input line voltage: 120-277V
- CRI: 90
- Powerfactor >0.9
- Dimmable: 0-10V
- Beam Angle: 110°
- Operating temperature: 5°F - 113°F
- 5 Year Warranty
- Finish: White
- Optional for Purchase: Emergency Driver, Pre-Mounting Plates, T-Bar

ACCESSORIES


Emergency Driver


Pre-Mounting Plate - 6"


Pre-Mounting Plate - 8"


Pre-Mounting Plate - 3/4/6/8"


T-Grid Hanger for Emergency



SAMPLE NUMBER LED6CRL15SW-127L9CCT3/MV

STYLE	DIAMETER	SERIES	WATTAGE	LUMEN	CRI	COLOR TEMP	VOLTAGE
LED led lighting	6 6 inch	CRL commercial downlight	15SW <15W selectable wattage	127L <1,270 Lumens	9 CRI90	CCT3 selectable color temperature	MV multiple voltage 120-277V

ENERGY STAR · IC RATED · JA8 · UL CERTIFIED · TITLE 24 · FC · LM 79 · LM 80 · RoHS Compliant

© 2022 naturaLED® All rights reserved
www.naturaLED.com Toll-Free: 855.758.7009

ORDERING

Watts (W)	Ordering Code	Description	CCT (K)	Lumens (Lm)	Equiv. Wattage (W)	Wet Location	Energy Star
9/12/15	**9466**	LED6CRL15SW-127L9CCT3/MV	3/4/5000K	760/ 1,020/ 1,275	60-150	•	•
12/19/27	**9467**	LED8CRL27SW-243L9CCT3/MV	3/4/5000K	1,440/ 1,890/ 2,430	100-200	•	•
17/20/30	**9468**	LED10CRL30SW-270L9CCT3/MV	3/4/5000K	1,620/ 2,070/ 2,700	150-250	•	•

ACCESSORIES (Ordered Separately)



Emergency Driver
7337 BAEM25-170BC/347-C
(25W Micro Inverter 120-347V with 12" Conduit)



T-Grid Bar/ Hanger
P10426 MT-TBAR-EM-2ft
(T-Grid Hanger for Emergency Driver)



6" Round Pre-Mounting Plate
P10309 PLT-NC/6DL
(6" Round Pre-Mounting Plate)



8" Round Pre-Mounting Long Plate
P10318 PLT-NC/8DL-LONG
(8" Round Pre-Mounting Long Plate)



Plate for 3/4/6/8" Disk Light
P10375 PLT-NC-DL/3-4-6-8
(Universal Plate for 3/4/6/8" Disk Light)

DIMENSIONS

9/12/15W (6-inch)
1.29-lbs



12/19/27W (8-inch)
1.73-lbs



17/20/30W (10-inch)
1.98-lbs



PHOTOMETRICS CHART

9/12/15W (6-inch)
Energy Star





12/19/27W (8-inch)
Energy Star





17/20/30W (10-inch)
Energy Star





PACKAGE

Case Qty
5 pcs



© 2022 naturaLED® All rights reserved