

SYLVANIA

LEDVANCE Luminaires LED

Traditional Ceiling Dome



Product Features

The Flush Mount Series are environmentally preferable LED alternatives to traditional CFL or Incandescent luminaires, offering up to 73% in energy savings. Ideal in place of traditional luminaires, or as new installations, the Flush Mount Luminaires can be used in residential, educational, property management or hospitality applications.

The Traditional Ceiling Dome offers integrated LED technology in a traditional form factor. This luminaire provides soft, even illumination through a frosted glass lens. LEDVANCE luminaires assure optimum light engine performance for extended service and rated life ($\geq 35,000$ hours L_{70}).

Catalog #	Type
Project	
Notes	
Date	
Prepared by	

Specifications

Weight: 3bs (1.4kg)

Construction: Aluminum back plate with a frosted glass lens. The standard finish is brushed nickel or oil rubbed bronze.

LED System: LED system with a life rating of $\geq 35,000$ hours at L_{70} @25°C.

Luminaire efficacy up to 47 LPW.

Electrical: Offered in 20 Watts, the luminaire is designed to operate at 120V with driver on board. The power factor is $\geq 80\%$ and THD is $\leq 20\%$.

Dimming: The driver is phase-cut dimmable (down to 10%).

Color Characteristics: CRI > 80 ; CCT of 2700K

Optics: Frosted glass lens.

Installation: Luminaire mounts to recessed outlet box.

Operating Temperature: -4°F to +104°F (-20°C to +40°C)

Listings: cETLus listed to UL1598 standards and suitable for dry locations.

Warranty: Standard 5-year luminaire warranty (LEDLUM001).

Note: Specifications subject to change without notice.



Ordering Information

Item Number	Product Name	Power (W)	Input Voltage	Dimming	CRI	Color Temp (CCT)	Total Fixture Lumens	LPW	Size (in)	Shape
74302	LEDFLUSHDOME11IN20DIM827BN	20	120V	Phase-Cut	> 80	2700K	1000	47	11	Round

*For further information and to learn more about utility rebates, contact your local SYLVANIA sales representative.