SATCO | NUVO

Project / Job Name:

Location:

Fixture Type:

Notes:



**S11967** - 30 Watt T8 LED; 6 Foot; 6500K; Recessed Double Contact base; 50000 Average rated hours; 4200 Lumens; Type B; Ballast Bypass; Double Ended Wiring

DAMP LOCATION · ENCLOSED FIXTURE · CLASSIFIED cULus · FC · RoHS COMPLIANT · 50,000 HOURS · 160° BEAM · TYPE B · 5 YEAR WARRANTY · 120-277V · IP 20 · NSF

## GENERAL

| | |
|---|---|
| Company | SATCO |
| EA Height | 1.1 |
| EA Width | 1.1 |
| EA Length | 72.0 |
| Lamp Ballast Type AB | Type B |
| Ballasting Requirements | Ballast Bypass |
| Lamp Filament | LED |
| Material | Glass |
| Fixture Type | Linear |
| Status | Active |
| Style | Utility |
| Surge Protection | Built-in-surge protection - 0.7KV |
| Total Harmonic Distortion | 25% |
| Tube Guard Use | Yes |
| CCT Selectable | No |
| Wattage Selectable | No |
| Finish Family | White |
| Amps | 0.250-0.108A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | White |
| Lens Material | Glass |
| Nominal Length | 72.0 |
| Operating Position | Universal |
| Power Factor | 0.9 |
| SDS Class | LED_Lamp |
| Shatter Proof Type | PET Coated |
| Indoor Outdoor | Indoor, Outdoor |
| Product Technology | LED |
| Fluor Equiv | 87W |
| Incandescent Equivalent | 125W |
| Serviceable Battery | No |
| Battery Indicator | No |
| Digital Display | No |

## ELECTRICAL

| | |
|---|---|
| CCT (Kelvin Temp) | 6500K |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 160 |
| Color Temp | Daylight |
| CRI | 80+ |
| Operating Frequency | 50/60Hz |
| Operating Temp | -4F to +113F (-20C to +45C) |
| Lumens | 4200L |
| Volts | 120V-277V |
| Watts | 30W |

## PHYSICAL

| | |
|---|---|
| Lamp Base | Recessed Double Contact HO/VHO |
| Finish | WHITE |
| Housing Color | White |
| ANSI Base | R17d |
| Lamp Type | T8 |
| MOD Lamps | 1.1 |
| MOL | 70.0 |

## ADDITIONAL INFO

| | |
|---|---|
| Warranty | 5-Years |
| Installation Notes | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | Yes |

## PACKAGING

| | |
|---|---|
| UPC | 045923119675 |
| Case Cube | 1.6716 |
| Case Height | 4.92 |
| Case Length | 74.6 |
| Case Quantity | 10 |
| Case UPC | 10045923119672 |
| Case Weight | 11.0 |
| Case Width | 7.87 |
| EA Cube | 0.0504 |
| EA Height | 1.1 |
| EA Length | 72.0 |
| EA Quantity | 1 |
| EA Weight | 1.03 |
| EA Width | 1.1 |
| Pack Type | Egg Crate |
| Web Length | 70.0 |
| Web Width | 1.1 |

## COMPLIANCE

| | |
|---|---|
| Bug Rating | B0-U0-G0 |
| FCC Compliant | Yes |
| IP Rating | IP20 |
| Location Rating | Damp |
| NSF Approved | Yes |
| ROHS Compliant | Yes |
| Safety Listing | cRUus - Recognized Component, cULus - Certified, cULus - Classified |
| California Ban | Lawful for sale |
| DLC Approved | No |
| Title 20 | Exempt |
| T24/JA8 Compliant | No |



© Satco Products, Inc.
All rights reserved 2026